Total Play Components 23 This play equipment is Drawn By: recommended for **Elevated Play Components** 20-164339 Scale: 5/32" = 1'-0" children ages: Elevated Play Components Accessible by Ramp | 0 | Req. Date: This drawing can be G 5-12 12/7/2023 scaled only when in A PLAYCORE Compar Elevated Components Accessible by Transfer an 11" x 17" format 544 Chestnut Street Quote Number: Minimum Area Required: Accessible Ground Level Components Shown 12 Req. Chattanooga, TN 37402 Play & Park Structures 48'-0" x 49'-2" 20-164339 800-727-1907 / www.playandpark.com Different Types of Ground Level Components 48'-0" **SUPER** 1,884 SQ FT INSIDE AREA 160 LINEAR FT 1,760 SQ FT MINIMUM **SURFACING** 12' SPIRAL TUBE SLIDE (REVERSE) 71947 ANGLE ROCK SOCKET RIGHT 67045 DENALI TOWER BASE 71930 12' SPIRAL TUBE SLIDE (REVERSE) BUTTON STEP 20" 65281 LARGE ALPINE CLIMBER 71878 OFFSET ENTRY BUTTON STEP MAZE PANEL 71750 STRETCHY CLIMBER 67032 BUTTON STEP 20" 65281 TRI-NET CLIMBER 67025 METAL HANDHOLD BARRIER TRIPLE ACTIVITY PANEL 71038 TELEPHONE 71013 – PARAGON TUBES 71380 49'-2" FUNNEL TRIANGLE TRANSFER POINT W\ BARRIER S-CURVED UPRIGHT 67057 CHUNNEL LINK > 71910 BUBBLE 71476 12' LEAN PIPE WALL 71014 BENCH SEAT 71249 PANEL BARRIER 71939 ATELEPHONE OUT PANEL 71941 VIRTUAL TUNNEL w/KNOT CLIMBERS 67024 HYBRID MAXCLIMB 6' HIGH QUEST LINK 71752 VORTEX CLIMBER 71741 SLIDE. SLIDE SUPPORT 71678 SUPPOR 71678 AURA ESCAPE 67040 ANGLE ROCK SLIDE, w/COLUMN SUPPORT 67052 SUPPORT 71678 ANGLE ROCK SOCKET RIGHT 67045 71677 71715 71732

It is the manufacturer's opinion that the structure shown herein complies with current ada standards concerning accessibility if used with proper accessible surfacing and together with other necessary ground level play equipment. Top View drawings and measurements are for overall site and structure appearance purposes. Top view should not be conceived as a construction detail; therefore, all measurements and slope requirements should be field verified prior to construction. IMPORTANT: Never install play equipment over hard, unresilient surfaces such as asphalt, concrete, or compacted earth. It is the owner's responsibility to ensure the "minimum area required" contains an appropriate amount of resilient material to cushion accidental falls.

10

20

TRIPLE ENTRANCE CASCADE W/ DECKS

75-85 Critical Fall Height 12'-0"

User Capacity

Req.

Req.

1 S O 9 0 0 1