











Product Name:	9FT Pyramid Net
Model Number:	YP295
Size:	Length: 14' 2"
	Width: 12' 4"
	Height: 10' 1"
Fall Height:	6'
Foundations:	5
Concrete Volume:	2.8 cubic yards
COMPLIANT	ASTM F-1487
WITH:	CSA Z614
Free standing flexible cl	imbers are compliant to ASTM F1

Free standing flexible climbers are compliant to ASTM F1487 and CSA Z614 for use by preschool age groups (2-5 years or 18 months-5 years respectively). The US CPSC does not recommend freestanding flexible climbers for these age groups groups

Ages:	2-5 or 5-12 years
Use Zone:	Length: 26' 2"
	Width: 24' 4"

Technical Details:	
Support Posts	This will be 5-1/2" (140mm) OD steel tubing, after fabrication shall be powder coated in accor- dance with the specifications herein.
Post Shields	Where required, these will completely surround the post to fill in openings in the net, preventing entrapments. Shields will be made of a textile-reinforced flexible rubber material and secured with hardware.
Climbing Nets	20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.
Rope Ball Con- nectors and End Fittings	One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.
Flexible Surfaces	5/16"(8mm) thick textile-reinforced rubber belt.
Fasteners	All fasteners shall be stainless steel with locking patch or locking compound (by others).
Turnbuckles	These will be steel alloy that will withstand a maximum load of over 87,675 pounds force (390 kN) along the main axis.
Installation	Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.