




Product Name: Model Number:	8ft Pyramid Net YP296
Size:	Length: 14' 4" Width: 14' 4" Height: 9' 1"
Fall Height:	5'
Foundations:	5
Concrete Volume:	3.4 cubic yards
COMPLIANT	ASTM F-1487
WITH:	CSA Z614
Eroo standing flovible d	imbors are compliant to AST



Free standing flexible climbers are compliant to ASTM F1487 and CSA Z614 for use by preschool age groups (2-5 years or 18 months-5 years respectively). The US CPSC does not recommend freestanding flexible climbers for these age groups

Ages:	2-5 or 5-12 years
Use Zone:	Length: 26' 4"
	Width: 26' 4"

Technical Details:	
Support Posts	This will be 5-1/2" (140mm) OD steel tubing, after fabrication shall be powder coated in accor- dance with the specifications herein.
Post Shields	Where required, these will completely surround the post to fill in openings in the net, preventing entrapments. Shields will be made of a textile-reinforced flexible rubber material and secured with hardware.
Climbing Nets	20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.
Rope Ball Con- nectors and End Fittings	One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.
Flexible Surfaces	5/16"(8mm) thick textile-reinforced rubber belt.
Fasteners	All fasteners shall be stainless steel with locking patch or locking compound (by others).
Turnbuckles	These will be steel alloy that will withstand a maximum load of over 87,675 pounds force (390 kN) along the main axis.
Installation	Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.