




Product Name: Model Number:	14ft Pyramid Tower YP301
Size:	Length: 25' 6"
	Width: 25' 6"
	Height: 14' 10"
Fall Height:	7'
Foundations:	5
Concrete Volume:	3.9 cubic yards
COMPLIANT	ASTM F-1487
WITH:	CSA Z614
Ages:	5-12 years
Use Zone:	Length: 37' 6" Width: 37' 6"



Technical Details:	
Support Posts	This will be 5-1/2" (140mm) OD steel tubing, after fabrication shall be powder coated in accor- dance with the specifications herein.
Post Shields	Where required, these will completely surround the post to fill in openings in the net, preventing entrapments. Shields will be made of a textile-reinforced flexible rubber material and secured with hardware.
Climbing Nets	20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel re- inforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. 22mm edge ropes will contain a solid core of wound steel cables in place of the polyamide core for a total of 168 steel reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.
Rope Ball Con- nectors and End Fittings	One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.
Flexible Surfaces	5/16"(8mm) thick textile-reinforced rubber belt.
Fasteners	All fasteners shall be stainless steel with locking patch or locking compound (by others).
Turnbuckles	These will be steel alloy that will withstand a maximum load of over 87,675 pounds force (390 kN) along the main axis.
Installation	Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.