







Product Specification

Product Name: Quad Slack Bridge

Model Number: YP344

Size: Length: 22' 4"

Width: 8' 6" Height: 1'6"

Fall Height: Foundations:

Concrete Volume: 0.8 cubic yards **COMPLIANT ASTM F-1487** WITH: CSA Z614

Ages: 5-12 years Use Zone: Length: 34' 4"

Width: 20' 6"



Technical Details:

Climber Frame Main supports shall be 4" (114mm) diameter steel tubing. After fabrication the frame shall be

powder coated in accordance with the specifications herein.

20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel Climbing Nets

reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.

Rope Ball Con-One-piece compressed aluminum ball connector or end fitting, compressed in place with

nectors and End 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear **Fittings**

Shall be made from min. 3/4" (19mm) thick high density, UV-stabilized and color impregnated Decking

polyethylene.

Fasteners All fasteners shall be stainless steel with locking patch or locking compound (by others).

Tensioning is achieved by way of a galvanized shackle and stainless steel eyebolt located at Tensioning

each Climber Pipe Junction capable of drawing the cables a minimum of 4"(100mm)

Polyester (Powder) Coating - The polyester coating shall be uniformly applied by the electro-Metal Finish

static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester

coating shall be from the manufacturer's standard color selection.

Installation recommended by a licensed playground contractor, trained and certified on the Installation

applicable playground installation methods and standards, preferably certified by manufacturer

or National Playground Contractors Association.

Concrete Achors Supplied by others.