




Product Name: Model Number: Size:	18ft Pryamid Tower Bridge YP303 Length: 32' 6" Width: 32' 6" Height: 18' 11"
Fall Height:	7'
Foundations:	5
Concrete Volume:	3.9 cubic yards
COMPLIANT	ASTM F-1487
WITH:	CSA Z614
Ages: Use Zone:	5-12 years Length: 44' 6" Width: 44' 6"



Technical Details:	
Support Post	This will be 5-1/2" (139.8mm) diameter steel tubing, which after fabrication shall be powder coated in accordance with the specifications herein.
Climbing Nets	20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel re- inforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. 22mm edge ropes will contain a solid core of wound steel cables in place of the polyamide core for a total of 168 steel reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.
Rope Ball Connec- tors	One-piece compressed aluminum ball connector, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.
Rope End Fittings	One-piece compressed stainless steel end fitting.
Turnbuckles	These will be steel alloy that will withstand a maximum load of over 87,675 pounds force (390kN) along the main axis.
Flexible Surfaces	3/8" (10mm) thick textile-reinforced rubbber belt.
Fasteners	All fasteners shall be stainless steel with locking patch or locking compound.
Metal Finish	Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electro- static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.
Installation	Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.