





Product Name: *Riptide*
Model Number: *YP451*
Size: Length: 30'-8"
 Width: 25'-10"
 Height: 7'-10"
Fall Height: 8'
Foundations: 27
Concrete Volume: 6.9 cubic yards
COMPLIANT WITH: ASTM F-1487
 CSA Z614
Ages: 5-12 years
Use Zone: Length: 42'-8"
 Width: 37'-10"



Technical Details:

Frame

Main Structure shall be 5-1/2" (139.8mm) diameter steel tubing, which after fabrication shall be powder coated in accordance with the specifications herein.

Climbing Nets

20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.

Rope Ball Connectors

One-piece compressed aluminum ball connector, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.

Rope End Fittings

One-piece compressed stainless steel end fitting.

Flexible Surfaces

3/8" (10mm) thick textile-reinforced rubber belt.

Fasteners

All fasteners shall be stainless steel with locking patch or locking compound.

Metal Finish

Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electro-static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.

Installation

Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.