









Date:06/28/24



Product Name: Model Number:	Roundabout YP464	
Size:	Length: 17'-1"	
	Width: 8'	
	Height: 5'-11"	
Fall Height:	5'	
Foundations:	13	
Concrete Volume:	6.7 cubic yards	
COMPLIANT	ASTM F-1487	
WITH:	CSA Z614	
_		
Ages:	5-12 years	
Use Zone:	Length: 29'-1"	
	Width: 20'	

Technical Details:		
Frame	Main Structure shall be 5-1/2" (139.8mm) diameter steel tubing combined with 4-1/2" (114.3mm) diameter steel tubing and 3" (75mm) diameter steel tubing, which after fabrication shall be powder coated in accordance with the specifications herein.	
Climbing Nets	20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating.	
Rope Ball Connec- tors	One-piece compressed aluminum ball connector, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear.	
Rope End Fittings	One-piece compressed stainless steel end fitting.	
Fasteners	All fasteners shall be stainless steel with locking patch or locking compound.	
Metal Finish	Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electro- static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection.	
Installation	Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association.	